



## Generell informasjon

Type armatur	
Materiale	Pulver lakkert aluminiumstøp
Lysstyring	Faseavsnitt
Netto / Brutto vekt armatur	4,51kg / 5,06kg
Forpakkingsstørrelse [cm]	22,3x12,8x87
Driver	Philips Xitanium 10W 0,5A 20V TE SC 230V (Produktblad/FDV)
Effekt W	5,8W
Armatureffekt	7,7W
Modul lumen	828lm
Lumen ut	634lm
Modul effektivitet	142,8lm/W
Armatur Lumen/Watt	82,3lm/W
ULOR	1%
Fargetemperatur	3000K
Farvekonsistens (McAdam-Ellipse)	SDCM3
Fargegjengivelsesindeks	80
Beregnet levetid L70/B50 ved 25°C	>109 000h
LED fotobiologisk trussel	RG0 or RG1
Energieffektivitetsindeks (EEL)	<b>A++</b>
Virkningsgrad	PF > 0,95
THD-faktor	< 20%
Ta nominel:	+25°C
Maksimal omgivelsestemperatur	+40°C
Inrush current	3,36A/36µs
Antall armaturer på automatsikring	<b>B 10A:</b> 126, <b>B 16A:</b> 200, <b>C 10A:</b> 208, <b>C 16A:</b> 340

## Filer som kan lastes ned

Photometric LDT files, Photometric IES files, Manual