

# Datablad/FDV

<b>Produkt</b>	Tetningsmasse 1 l/1 kg
<b>El nr</b>	1167456
<b>Type</b>	1L
<b>EAN</b>	7070701077222
<b>Antall</b>	1
<b>Salgsenhet</b>	Stk



## PRODUKTBESKRIVELSE

Isolasjon og tetting av koblingsbokser, kanaler etc. God korrosiv beskyttelse. IP68. 2-komponent fleksibel silikon isolasjons- og tetningsmasse, type M-G. Herdetid kun 2 - 10 minutter, avhengig av omgivelsestemperatur. (ca. 10 min. ved 18 grader C) Halogenfri.

Standard: HD 623

## TEKNISKE SPESIFIKASJONER

Skjøter 1KV

Characteristics and Performance	
Characteristics	Performance
Non toxic and safe	Professional INSULATION high dielectric strength and volume resistivity
Fast in cross linking (<10 min), without temperature increase	HIGH THERMAL CHARACTERISTICS at both high or low temperatures, typical for energy installations.
It cross links also at low temperature	SEALING complies with CEI 20-33 and CENELEC EN 50393
Low viscosity	SINGLE SYSTEM CERTIFICATE for electrical connection insulations complying with standards EN 50393 and CEI 20-33 (Note with testing under water head and water between the cable cores)
Operating temperature: -60/+200°C	
Re-enterable also after long working periods.	
Without shelf-life	
Very high dielectric characteristics	
Dielectric strength: >23 kV/mm	
Volume resistivity: >2.10 <sup>15</sup> Ω cm	
Innhold ml	1000